

ERXS-17

1U High Resolution 17" Sun-Specific Rackmount LCD
with Notebook Keyboard, Touch Pad & Optional KVM



Generation 4

General Information

Form Factor	: 1U Rackmount
Mounting Type	: 4 Post/Cabinet (2 Post Available)
Number of Drawers	: 1
LCD Access	: Clamshell Style
Model Version	: Generation 4 (Gen4)
Pointing Device	: Touch Pad (Track Ball Available)
Color	: Black (Custom Available)
Hardware Supported	: Multi-Platform
Regulatory Approval	: CE, FCC, RoHS
Warranty	: 2 Years (Extended Available)

LCD

Display Size	: 17.1" Widescreen TFT
Ratio	: 16:10
LCD Manufacturer	: LG
LCD Type	: Grade A Industrial TFT LCD Panel
Backlighting	: LED
Resolution	: 1920x1200
Display Color	: 16.7M, 8-bit
Brightness	: 210 cd/m ²
Contrast Ratio	: 600:1 typical
Active Area (mm)	: 367x230
Viewing Angle	: 130° / 110°
Signal Input	: VGA, DVI-D, HDMI
MTBF	: 20,000 hours

Sun-Specific Features

Direct Resolution	: 1152x900
Hotkey Commands	: Stop, Again, Props, Undo, Find, Open, Copy, Cut, Paste, Front, Help, Sleep

KVM

Number of Ports	: 8 (Std) / 12 (DVI-D) / 16 (Std)
Maximum Cascade	: 8 Levels (64-128 Servers) Std Only

Remote IP Option

Number of IP Ports	: 1
User Management	: 15-User Login; 1-4 Active Users Possible
Security	: SSL v3, RSA, AES, HTTP/HTTPS, CSR
IP Access	: 1 x RJ45 Ethernet, 1 x DB9 Serial, 1 x USB

Power Adapter

Input	: 100-240VAC~1.5A Max 50/60Hz
Output	: 12V~4.0A
Consumption	: Max 48 Watts
Internal/External	: Internal IEC-Type C13 (Single); External/Brick (DVI KVM)
Optional DC	: 12V / 24V / 48V DC Input Available

Environmental

Temperature	: 0 to 50 Degree Celsius (Operation) : -5 to 60 Degree Celsius (Storage)
Relative Humidity	: 5~90%, Non-Condensing
Shock	: 10G Acceleration (11ms Dur, Half Sine)
Vibration	: 5~500Hz 1G RMS Random Vibration

Mounting Depth

w/ VGA, DVI-D	: 2.5" to 5.5" (2 Post, 12" Brackets)
w/ VGA, DVI-D	: 16.25" to 26" (4 Post, 12" Brackets)
w/ VGA, DVI-D	: 18.9" to 29.5" (4 Post, 16" Brackets)
w/ DC Power	: 21" to 32" (4 Post, 16" Brackets)
w/ KVM	: 23.5" to 34.5" (4 Post, 16" Brackets)

Dimensions & Weight

w/ VGA, DVI-D	: 17.4" W x 1.73" (1U) H x 18.9" D; 24 lbs.
w/ VGA, DVI-D	: 17.4" W x 1.73" (1U) H x 18.9" D; 24 lbs.
w/ VGA, DVI-D	: 17.4" W x 1.73" (1U) H x 18.9" D; 24 lbs.
w/ DC Power	: 17.4" W x 1.73" (1U) H x 19.7" D; 25 lbs.
w/ KVM	: 17.4" W x 1.73" (1U) H x 22.8" D; 26 lbs.



ECLIPSE RACKMOUNT
INDUSTRIAL RACKMOUNT PROFESSIONALS

Eclipse Rackmount, Inc.

(888) ECL-RACK (325-7225) | (415) 895-1570 Direct | (415) 727-4000 FAX